

Technical Information

No. FO 4134

Edition: 06/02 - subject to change

Substitutes: Edition 10/98
Status: valid

Mercury Short Arc Lamp
for Microlithography

HBO[®] 500 W/B

■ Product description

The OSRAM HBO[®] 500 W/B is especially optimized for constant power DC-operation. The lamp emits high radiant intensity in the UV and adjacent visible wavelength range. The HBO[®] 500 W/B distinct features are the high optical quartz glass quality and outstanding arc stability combined with a long service life.

■ Technical data

Order reference		HBO [®] 500 W/B
Rated lamp wattage	W	500
Rated lamp voltage	V	48.5
Rated lamp current (=)	A	10.3
Ignition voltage	kV _s	max. 15
Radiant power wave-length range 350-450nm	W	60
Radiant intensity wave-length range 350-450nm	mW/sr	5,800
Average luminance	cd/cm ²	64,000
Electrode gap e	mm	3
Lamp length l ₁	mm	max. 180
Lamp length l ₂	mm	150 / max. 151.5
Bulb diameter d	mm	29
LCL a	mm	78.5
Guaranteed life	h	800

Base

- Cathode: SFcY 13-5/20 ka hexagon base with thread M5
- Anode: SXFc 13-5/20 with thread M5

■ Lamp operation

Maximum permissible base temperature °C 200

Cooling Convection

Burning position vertical, Anode (+) underneath

■ Safety Instruction

Due to their high luminous efficacy, the UV radiation which they emit and the high pressure within the lamp, HBO[®] lamps must be operated within enclosed, purpose-built housings. When a lamp breaks, mercury is released. Particular safety regulations must be paid attention (for details please request technical information sheet no. FO 4574).

